

STALWART

Thermostatic Water Bath STW-1015



Introduction

Thermo shaker incubator has fast mixing speed. Combined with intelligent operation, it can not only mix various tubes, PCR plates, deep-well plates, micro plates and other laboratory supplies, but also equip the function of vortexing and heating (cooling) all kinds of tubes to meet different needs of different users

Features

- Perfect radius and excellent 2 dimensional blend technology with adjustable mixing speed.
- Programmable. Efficient shaking and temperature control.
- Multiple safety protection. Fit for CE safe standard, safety and reliable.
- Microprocessor and good linearity of temperature control. Shaking speed is accurate with small fluctuations.
- Timing function. Time range is from 0 to 100hours. Non-stop operation time to run continuously is also available.
- Various blocks to exchange, convenient for replacement.
- Built-in temperature calibration function and short mixing function.
- DC brushless motor drive, long life and free of maintenance.
- Power recovery function. After power restored instrument can be set to automatically restore the original run.(STC-100)

Specification

Item	STW-1015
Timing range	1~99h59min (0 is forever)
Temp. range	RT.+5°C~100°C
Temp. accuracy	±0.5°C
Temp. Uniformity@37°C	±0.5°C
Number of holes	1
Volume	15L×1
Workspace	500×300×95mm×1
Voltage	AC 220V 50/60Hz
Power	2200W
Dimensions	W.570×D.365×H.465mm
Net weight	13.6kgs